














Rv.4 10\_12\_2021

Name	Liso	Natté	Solids
Composition	100% acrylic	100% acrylic	100% acrylic
Weight (ISO 3801 – UNI 5114)	260 g/m <sup>2</sup>	275 g/m <sup>2</sup>	260 g/m <sup>2</sup>
Abrasion (Martindale)- (ISO 12947-2)	20000 cycles	30000 cycles	30000 cycles
Abrasion Wool abradant (ISO 5470-2)	-	-	-
Colour fastness to UV light (ISO 105 B02)	7 out of 8	8 out of 8	8 out of 8
Colour fastness to UV light (ISO 105 B04)	4 out of 5	4-5 out of 5	4-5 out of 5
Colour fastness to washing at 40°C (ISO 105 C06)	5 out of 5	5 out of 5	5 out of 5
Finishing	Stain resistant – Mould proof	Stain resistant – Mould proof	Stain resistant – Mould proof
Classification	Water-repellent	Water-repellent	Water-repellent
Care			
Recommended use	Outdoor	Outdoor	Outdoor
Notes	Cold wash		



Name	Bruma	Lopi	Trama	Panama
Composition	100% acrylic	100% acrylic	100% acrylic	100% acrylic
Weight (ISO 3801 - UNI 5114)	400 g/m2	680 g/m2	640 g/m2	280 gr/m2
Abrasion (Martindale)- (ISO 12947-2)	25000 cycles	90000 cycles	-	20000 cycles
Abrasion Wool abradant (ISO 5470-2)	-	-	-	-
Colour fastness to UV light (ISO 105 B02)	7 out of 8	8 out of 8	7 out of 8	7 out of 8
Colour fastness to UV light (ISO 105 B04)	4 out of 5	4 out of 5	-	4 out of 5
Colour fastness to washing at 40°C (ISO 105 C06)	5 out of 5	5 out of 5	5 out of 5	-
Finishing	Stain resistant - Mould proof	Stain resistant - Mould proof	Stain resistant - Mould proof	Stain resistant - Mould proof
Classification	Water-repellent	Water-repellent	Water-repellent	Water-repellent
Care				
Recommended use	Outdoor	Outdoor	Outdoor	Outdoor
Notes				

# RANGE 3



Name	Patio	Zagora	Atrium	Erfoud
Composition	100% Trevira CS	100% acrylic	100% Trevira CS	100% acrylic
Weight (ISO 3801 – UNI 5114)	560 g/m2	830 g/m2	510 g/m2	630 g/m2
Abrasion (Martindale)- (ISO 12947-2)	50000 cycles	40000 cycles	50000 cycles	50000 cycles
Abrasion Wool abradant (ISO 5470-2)	-	-	-	-
Colour fastness to UV light (ISO 105 B02)	7 out of 8	7 out of 8	6 out of 7	7 out of 8
Colour fastness to UV light (ISO 105 B04)	4-5 out of 5	-	5 out of 5	-
Colour fastness to washing at 40°C (ISO 105 C06)	5 out of 5	-	5 out of 5	-
Finishing	Stain resistant – Mould proof	Stain resistant – Mould proof	Stain resistant – Mould proof	Stain resistant – Mould proof
Classification	Water-repellent	Water-repellent	Water-repellent	Water-repellent
Care		 Iron at low temperature		 Iron at low temperature
Recommended use	Outdoor	Indoor/Outdoor	Outdoor	Indoor/Outdoor
Notes	Flame retardant	Iron at low temperatures	Resistant to chlorine / Flame retardant	Iron at low temperatures

Name	Cima	Kelso
Composition	100% acrylic Solution dyed	100% acrylic
Weight (ISO 3801 – UNI 5114)	650 g/m <sup>2</sup>	670 g/m <sup>2</sup>
Abrasion (Martindale) (ISO 12947-2)	20000 cycles	20000 cycles
Abrasion Wool abradant (ISO 5470-2)	-	-
Colour fastness to UV light (ISO 105 B02)	7 out of 8	7 out of 8
Colour fastness to UV light (ISO 105 B04)	-	-
Colour fastness to washing at 40°C (ISO 105 C06)	-	-
Finishing	Stain resistant – Mould proof	Stain resistant – Mould proof
Classification	Water-repellent	Water-repellent
Care	 <b>Iron at low temperature</b>	 <b>Iron at low temperature</b>
Recommended use	Indoor/Outdoor	Indoor/Outdoor
Notes	Iron at low temperatures	Iron at low temperatures

# LAMINATED - WATERPROOF

Name	Liso Laminated	Solids Laminated
Composition	100% acrylic foil 100% PU	100% acrylic foil 100% PU
Weight (ISO 3801 - UNI 5114)	290 g/m <sup>2</sup>	300 g/m <sup>2</sup>
Abrasion (Martindale)- (ISO 12947-2)	15000-20000 cycles	20000 cycles
Abrasion Wool abradant (ISO 5470-2)	-	-
Colour fastness to UV light (ISO 105 B02)	7 out of 8	8 out of 8
Colour fastness to UV light (ISO 105 B04)	4-5 out of 5	4-5 out of 5
Colour fastness to washing at 40°C (ISO 105 C06)	5 out of 5	5 out of 5
Finishing	Stain resistant - Mould proof	Stain resistant - Mould proof
Classification	Water-repellent	Water-repellent
Care		
Recommended use	Outdoor	Outdoor
Notes		




# OTHER FABRICS

Name	Felt	Leather
Composition	100% wool	80% regenerated leather 20% pure rubber
Weight (ISO 3801 – UNI 5114)	1800 g/cm <sup>3</sup> (DIN 61200)	-
Abrasion (Martindale)- (ISO 12947-2)	47000 cycles	-
Abrasion Wool abradant (ISO 5470-2)	NA	-
Colour fastness to UV light (ISO 105 B02)	NA	-
Colour fastness to UV light (ISO 105 B04)	NA	-
Colour fastness to washing at 40°C (ISO 105 C06)	NA	-
Finishing	Antipilling, Stain resistant	-
Classification	Water-repellent	-
Care	 Clean with damp cloth	
Recommended use	Indoor	Indoor
Notes	-	-

# FABRICS OUT OF PRODUCTION





Name	Narciso	Bella	Rasen
Composition	100% acrylic	100% polypropylene	50% polypropylene 50% polyester
Weight (ISO 3801 – UNI 5114)	720 g/m <sup>2</sup>	518 g/m <sup>2</sup>	415 g/m <sup>2</sup>
Abrasion (Martindale)- (ISO 12947-2)	25000 cycles	20000 cycles	15000 cycles
Abrasion Wool abradant (ISO 5470-2)	-	-	-
Colour fastness to UV light (ISO 105 B02)	7-8 out of 8	7-8 out of 8	7-8 out of 8
Colour fastness to UV light (ISO 105 B04)	-	-	-
Colour fastness to washing at 40°C (ISO 105 C06)	5 out of 5	4-5 out of 5	4-5 out of 5
Finishing	Stain resistant – Mould proof	Stain resistant – Mould proof	Stain resistant – Mould proof
Classification	Water-repellent	Permeable	Water-repellent
Care			
Recommended use	Outdoor	Outdoor	Outdoor
Notes			

# FABRICS OUT OF PRODUCTION

Name	Pure leather	Zen	Palazzo
Composition	100% cowhide	Support made from jersey Polyamide and PVC composite	100% acrylic
Weight (ISO 3801 – UNI 5114)	NA	780 g/m2	330 g/m2
Abrasion (Martindale)- (ISO 12947-2)	NA	>120000 cycles (ISO)	25000 cycles
Abrasion Wool abradant (ISO 5470-2)	-	-	-
Colour fastness to UV light (ISO 105 B02)	NA	-	8 out of 8
Colour fastness to UV light (ISO 105 B04)	-	-	4-5 out of 5
Colour fastness to washing at 40°C (ISO 105 C06)	NA	-	5 out of 5
Finishing	Stain resistant – Mould proof	Stain resistant – Mould proof	Stain resistant – Mould proof
Classification	-	Water-repellent	Water-repellent
Care		 Clean with a damp cloth and neutral soap	
Recommended use	Covered outdoor spaces	Outdoor	Outdoor
Notes			Cold wash



# FABRICS OUT OF PRODUCTION

Name	Heritage	Eco-leather	Robben	Sweet
Composition	50% recycled acrylic 47% acrylic 3% polyester	20% polypropylene 80% PVC	100% acrylic	33% cotton 63% PVC 4% polyurethane
Weight (ISO 3801 – UNI 5114)	335 g/m2	665 g/m2	630 g/m2	610 g/m2
Abrasion (Martindale)- (ISO 12947-2)	22000 cycles	15000 cycles	40000 cycles	-
Abrasion Wool abradant (ISO 5470-2)	-	-	-	>51200
Colour fastness to UV light (ISO 105 B02)	8 out of 8	7-8 out of 8	8 out of 8	Light 3/4 Dark 6/7
Colour fastness to UV light (ISO 105 B04)	4-5 out of 5	-	4-5 out of 5	-
Colour fastness to washing at 40°C (ISO 105 C06)	5 out of 5	-	5 out of 5	4-5 out of 5
Finishing	Stain resistant – Mould proof	Stain resistant – Mould proof	Stain resistant – Mould proof	Stain resistant – Mould proof
Classification	Water-repellent	Water-repellent	Water-repellent	-
Care		 Wash with damp cloth and neutral soap		 Wash with damp cloth and neutral soap
Recommended use	Outdoor	Outdoor	Outdoor	Covered outdoor spaces
Notes	Cold wash		Cold wash	FR 1.IM FR CRIB 5